

**SEMI-FLUSH FIXTURE /  
INSTALLATION INSTRUCTIONS**

Please read carefully and save these instructions, as you may need them a later date.

**CAUTION**

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

**GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections, obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

**ASSEMBLY AND INSTALLATION**

- 1, Attach the Screw-1 with the Hex Nut-1 to the Cross bar, then attach the Cross Bar to the Outlet Box by using 2 pcs Mounting Screws-2
  - 2, Make wire connections:
    - Smooth wire (w/markings) from the light to black wire from power source.
    - Ribbed wire (w/o markings) from the light to white wire from power source
    - Attach the ground wire to the cross bar with a green ground screw.
    - Carefully tuck wire back into the OUTLET BOX
  - 3, Place the Canopy against the Outlet box, secure with the Ball nut. Screw the Center pipe with the Hex Nut-2 to the Coupling, then screw the other Hex Nut-3, STATOR and another Hex Nut-3 in the mid of Center Pipe.
  - 4, Install bulbs. (Please do not exceed the maximum capacity which is recommended on the sockets).
  - 5, Attach the GLASS (GLASS SOLD SEPARATELY, Please adjust the Stator in a propriety position and have it fit the GLASS) to the fixture. Attach the RUBBER WASHER, METAL WASHER to the NIPPLE and screw with the HEX NUT-4, attach the bottom CAP to the GLASS and lock with Finial
- INSTALLATION IS NOW COMPLETED.

