

**CHANDELLIER FIXTURE
INSTALLATION INSTRUCTIONS**

Please read carefully and save these instructions, as you may need them a later date.

CAUTION


Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

1. Put the Cap onto the Nipple on the fixtures. Then Screw the Loop to the Fixture.
2. Attach the Cross Bar to the Outlet Box by using 2pcs Mounting Screws upwards. Screw the NIPPLE with the WASHER and HEX NUT to the CROSS BAR.
Make wire connections:
--Smooth wire (w/markings) from the light to black wire from power source.
--Ribbed wire (w/o marking) from the light to white wire from power source
--Attach the ground wire to the cross bar with a green ground screw.
Carefully tuck wire back into the OUTLET BOX
3. Screw the TOP LOOP to the NIPPLE, Place the CANOPY against the OUTLET BOX, and secure it with the TOP NUT.
4. Turn and adjust the Arm evenly, Attach the GLASS (GLASS SOLD separately) onto the Socket and secure with the Ring



ITEM NO. 205 BRZ & 209 BRZ