

**PENDANT FIXTURE  
INSTALLATION INSTRUCTIONS**

Please read carefully and save these instructions, as you may need them a later date.

**CAUTION**

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

**GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

**ASSEMBLY AND INSTALLATION**

- Connect the Pipe (1)(2)(3)(4)(5) together with the fixture. Then screw with the Swivel.
- Attach two Screws-1 outward through the CROSS BAR, spin the Hex nut to the Screw-1, then attach the CROSS BAR to the OUTLET BOX by the two MOUNTING SCREWS.
- Make wire connections:
  - Ribbed wire(w/o marking) from light to WHITE WIRE from power source
  - Smooth wire(w/ marking) from light to BLACK WIRE from power source
  - Loop the GROUND WIRE to CROSS BAR with a GREEN SCREW
- Place the CANOPY against the OUTLET BOX by screwing the Hex nut and Ball Nut
- Attach the GLASS SHADE(glass sold separately) onto the SOCKET, screwed RING.

