## ASSEMBLY AND INSTALLATION INSTRUCTIONS FOR ITEM #1324MBBN

WARNING

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Should any difficulty be experienced, please consult a qualified electrician before installing.

## **Installation steps:** OUTLET BOX BLACK WIRE WIRE CONNECTOR 1. Turn off the electricity at the Fuse or Circuit **GROUND WIRE** WHITE WIRE MOUNTING SCREW-1 Breaker before installation. ROUND BAR MOUNTING SCREW-2 2. Attach the Round Bar to the Outlet Box by **GREEN SCREW** using 2PCS of Long Mounting Screw-2 upwards. CANOPY FIXING NUT 3. Decide the amount of Rod sections needed for the desired SWIVEL height and attached those Rod sections together, then run the wire from the fixture through the Rod sections and ROD Connector into the Canopy, attached one end of Rod section to the Connector and the other end to the Swivel. 4. Make wire connections with Wire Connectors:. ----Connect the Wire (W/ marking) from the light to the Black Wire from the Outlet Box. ----Connect the Wire (W/O marking) from the light to the White RODS Wire from the Outlet Box. CONNECTOR **BULB** ----Attached the Ground Wire and House Ground Wire to the Cross Bar with a Green Screw. CANDLE COVER Carefully tuck wires back into the Outlet Box. SOCKET 5. Attached the Canopy to the Round Bar and secure with the Fixing Nuts to the Short Mounting Screw-1.

- 6. Install Bulbs. (Bulbs are not included, please do not exceed the maximum capacity which is recommended on the Candle Cover.)
- 7. Turn on the power at Fuse or Circuit Box and enjoy your new fixture.

