

ASSEMBLY & INSTRUCTIONS

**IMPORTANT! TO PREVENT ELECTRICAL SHOCK,
TURN OFF ELECTRICITY AT CIRCUIT BREAKER
OR FUSE BOX BEFORE PROCEEDING WITH INSTALLATION.**

Remove all parts and parts packages from carton.

1. Insert the fixture cord through the connector and secure the strain relief by threading the fixture cord through both holes. Set the desired height of fixture. Attach the plastic screw to the connector and secure tightly.
2. Thread the mounting screws into the opposite side of the mounting plate from the ground screw.
3. Guide fixture wires through hole in center of mounting plate.
4. Follow wiring instructions carefully (listed below).
5. Attach mounting plate to outlet box using box screws provided with outlet box.
6. Thread the hex nut onto mounting screws.
7. Split the conductors of the fixture wire about 4 inches. Being careful not to expose any of the wire inside of the insulation.
8. Connect the fixture ground wire to the outlet box ground wire using wire nut. Connect outlet box ground wire to mounting plate with GREEN hex-head ground screw to tapped hole in mounting plate marked "GND".
9. Connect the half of the fixture wire that is white, marked, or has a ribbed surface to the outlet box supply wire (WHITE). Connect the other half of the fixture wire that is black, unmarked, or has a smooth surface to the outlet box supply wire (BLACK or RED). Use wirenuts provided.
10. Spread the electrical splices so that the black wire are on one side of the outlet box and the white wire are on the other side.
11. Mount fixture by aligning mounting holes in canopy with mounting screws and threading ball nuts onto mounting screws.
12. Install bulb (not included).
13. Secure the glass to the glass hold.

The installation is now complete and power may be reconnected at the main fuse box.

