

**VANITY LIGHT FIXTURE  
INSTALLATION INSTRUCTIONS**

Please read carefully and save these instructions, as you may need them a later date.

**CAUTION**

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

**GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the Installation Instructions.

**ASSEMBLY AND INSTALLATION**

- 1, Thread the Screw-1 to the Cross bar, then screw the Hex nut on the Screw-1.
- 2, Attach the Cross Bar to the Outlet Box by 2pcs Mounting Screws
- 3, Make wire connections:
  - Smooth wire (w/markings) from the light to black wire from power source.
  - Ribbed wire (w/o markings) from the light to white wire from power source
  - Attach the ground wire to the cross bar with a green ground screw. Carefully tuck wire back into the OUTLET BOX
- 4, Place the Back plate against the Outlet box, secure with the Ball nut
- 5, Attach the lamp shade (Not Included, sold separately) and metal ring onto the socket, then screwed it on the socket by socket ring.
- 6, Install bulbs. (Please do not exceed the maximum capacity which is recommended on the sockets).

INSTALLATION IS NOW COMPLETED.

ITEM NO.: 5912-BN, 5912-MB

ITEM NO.: 5913-BN, 5913-MB

ITEM NO.: 5914-BN, 5914-MB

