ASSEMBLY AND INSTALLATION **INSTRUCTIONS FOR ITEM #832**

WARNING

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Should any difficulty be experienced, please consult a qualified electrician before installing.

- the Outlet Box
- ----Connect the White Wire from the light to the White Wire from the Outlet Box.
- ----Attached the Ground Wire and House Ground Wire to the Mounting Bar with a Green Screw. Carefully tuck wires back into the Outlet Box.

HEX NUT

FINIAL

- 4. Raise up the Ceiling Plate to the Mount Bar and secure the Ceiling Plate in place by threading the Fixing Nut to Mounting Screw-1 from the Mounting Bar firmly.
- 5.Install Bulbs . (Bulbs are not included, please do not exceed the maximum capacity which is recommended on the Socket Cover.)
- 6.Screw and adjust Center Tube to Connector, then attached the Glass, Plastic Washer, Hex nut, End Cap to the Ceiling Plate in order and secure the glass by threading the Finial to the exposed Thread of the Center Tube, making sure there is enough Center Tube bottom thread exposure to fix the glass with Finial.
- 7. Turn on the power at Fuse or Circuit Box and enjoy your new fixture.



PLASTIC WASHER

END CAP

